



**BULLARD  
BOLLARDS**  
Think Bollard Think Bullard



# MR. DOME DS

**K12**  
RATING

NON-ILLUMINATED **SECURITY & SAFETY BOLLARDS**

Fixture Type:

Project Name:



**General Information:**

---

A refined yet robust solution, MR. DOME DS combines a softened dome profile with dual reveal detailing to enhance both visibility and protection. It supports safer environments by clearly defining boundaries while maintaining a cohesive design language.

Engineered for performance and adaptability, it offers a range of security ratings and finishes for seamless integration.

Applications: public spaces, secure perimeters, mixed-use developments

**Fixture Type:**

---

Non-Illuminated Security & Safety Bollard

**Bollard Cover Materials:**

---

- Stainless Steel
- Aluminum
- Carbon Steel

**Finishes:**

---

- White
- Green
- Corten
- Grey
- Black
- Stainless Steel
- Custom on request

**IP Rating:**

---

IP 65



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.


**THINK BOLLARD - THINK BULLARD**

[sales@gordonbullard.com](mailto:sales@gordonbullard.com) / [www.bullardbollards.com](http://www.bullardbollards.com) / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA

Fixture Type:

Project Name:



**HOW TO ORDER:**

**CODE:**

**CODE EXAMPLE:**  
BB-MRD-SB-K12-H4-01-11

BB-MRD-SB-K12-  
H4-01-11

**1 BOLLARD DIAMETER:**

Diameter - Ø: 12" (30.48 cm)








**2 BOLLARD HEIGHT:**

- H1 H: 40" (101.6 cm)
- H2 H: 42" (106.6 cm)
- H3 H: 43.5" (110.4 cm)
- H4 H: 44.5" (113 cm)
- H5 H: 46" (116.8 cm)
- H6 H: 47.5" (120.6 cm)
- H7 H: 48" (121.9 cm)
- H8 H: 49" (124.4 cm)
- H9 H: 51" (129.5 cm)
- H10 H: 54" (137.1 cm)
- H11 H: 56" (142.2 cm)
- H12 H: 57" (144.7 cm)
- H13 H: 59" (149.8 cm)
- H14 H: 62" (157.4 cm)
- CUS Custom Height

**3 BOLLARD COVER MATERIALS:**

- 01 Stainless Steel,
- 02 Aluminum,
- 03 Carbon Steel

**4 FINISH OPTIONS:**

- 392 White 
- 393 Green 
- 394 Corten 
- 395 Grey 
- 396 Black 
- 11 Stainless Steel 
- CUS Custom on request\* 



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

**THINK BOLLARD - THINK BULLARD**

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646  
991 South Gull Lake Dr Richland, MI 49083 USA

## DOS K-RATING EXPLAINED

DOS K-ratings are a legacy U.S. Department of State crash-testing classification system used to define the performance of security barriers (such as bollards) against vehicle impact. The rating is based on a standardized test involving a 15,000 lb vehicle impacting at defined speeds—K4 (30 mph), K8 (40 mph), and K12 (50 km/h ≈ 50 mph)—with performance measured by how effectively the barrier stops the vehicle and limits penetration beyond the barrier line.



### DOS K12

- **Vehicle weight:** 15,000 lbs
- **Impact speed:** (50 mph)
- **Vehicle type:** medium-duty truck
- **Penetration:** 1 meter or less (L3)
- **Test standard:** U.S. Department of State (DOS) crash test protocol

## FOUNDATION OPTIONS EXPLAINED

Understanding foundation type and depth is critical to ensure the bollard performs as designed under impact. Improper installation can significantly reduce crash-rating effectiveness and compromise site safety.



### Deep Foundation

- **Excavation:** 47.25 in (1200 mm) depth
- **Reinforcement:** Rebar cage (#5 / #8)
- **Installation:** Bollard embedded and fully encased in concrete
- **Function:** Transfers impact load into deep concrete mass



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

**THINK BOLLARD - THINK BULLARD**

[sales@gordonbullard.com](mailto:sales@gordonbullard.com) / [www.bullardbollards.com](http://www.bullardbollards.com) / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA