



**BULLARD  
BOLLARDS**  
Think Bollard Think Bullard

**SLICK WILLY ABYSSLINE**  
BB-SLWLAL-CL





FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

-24V.3D1515.LAL



**GENERAL INFORMATION:**

Engineered for architectural excellence, this high-performance silicone neon LED delivers refined, shadow-free illumination with exceptional durability across demanding environments. Featuring a high-efficiency light source (LM80 certified) and a precision optical distribution design, it ensures perfectly uniform light with no visible dots or shadows; pure, continuous elegance. Crafted using an advanced three-color silicone extrusion process, the strip offers superior flexibility, clean cutting accuracy, and a sleek, dust-resistant finish. Compared to traditional PVC solutions, its premium silicone body provides enhanced resilience and a more sophisticated aesthetic. Built to endure, it resists UV exposure, corrosion, saline environments, acids, and alkalis, making it ideal for both indoor and outdoor architectural applications.

**FIXTURE TYPE:**

Arch LED Neon

**MATERIAL:**

Three-color silicone extrusion process

**IP RATING:**

IP67

IP67

**IK RATING:**

IK08

IK08

**WARRANTY:**

5 year warranty, high reliability

**DRIVER POSITION:**

Remote

**MAIN FEATURES:**

Light source: High luminous efficiency, LM80 proved.  
Optical Design: Unique optical light distribution structure design.  
Product Certification: UL, CE, ROHS, UKCA, CB  
Working/Storage Temperature: Ta:-25~50°C / 0°C~60°C.  
Product application: Signage lighting, Outdoor/indoor lighting, Architectural contour lighting.



**THINK BOLLARD - THINK BULLARD**

sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake Dr  
Richland, MI 49083  
USA



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_



**HOW TO ORDER:**

**CODE:**

**Example:**  
CODE: BB-SLWLAL-CL-24V.3D1515.LAL-27K-AS-AWS/  
T2020A-30

BB-SLWLAL-  
CL-24V.3D1515.LAL-  
27K-AS-AWS/  
T2020A-30

**1 DIMENSIONS:**

A) Length - L: 0.39" (1 cm)  
B) Height - H: 0.70" (1.8 cm)

**2 LIGHT SOURCE:**

	CCT	CRI	INPUT VOLTAGE	RATED CURRENT (A/m)	RATED POWER	MAXIMUM POWER	LUMENS
-27K	2200K	>90	DC24	0.4 (0.24A/ft)	10 (3.05W/ft)	11 (3.35W/ft)	520(159LM/ft)
-30K	3000 K						560(171LM/ft)
-40K	4000 K						630(192LM/ft)
-65K	6500 K						600(183LM/ft)

STANDARD LENGTH	REMARK
5000mm (16.4ft)	16LED/50mm



**THINK BOLLARD - THINK BULLARD**

sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake Dr  
Richland, MI 49083  
USA



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

**HOW TO ORDER:**

**CODE:**

Example:  
CODE: BB-SLWLAL-CL-24V.3D1515.LAL-27K-AS-AWS/  
T2020A-30

BB-SLWLAL-  
CL-24V.3D1515.LAL-  
27K-AS-AWS/  
T2020A-30

**3 ACCESSORIES:**

AS-AWS/T2020A-30



AS-AWS/T2020A-950



AS-FC-0031




AS-JD-0001



AS-PG-0004



AS-WS-0037



CP1-GBA



CP1-GBB



**THINK BOLLARD - THINK BULLARD**

sales@gordonbullard.com

www.bullardbollards.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA