

### CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	70mm(2.75")
Height / Projection:	70mm(2.75")

### ELECTRICAL:

### GH1110.LVFT300EN




Number of heads:	1
Description:	1 x 8 W LED 3000 K CRI>80 1 x 656 lm
Luminaire efficiency:	55.79 m/W
Fixture consumption:	9.41 W
Operation Range:	110-277 V - 50/60 Hz
Number of circuits:	1
Driver positioning:	Remote
Control gear type:	Electronic
Cable entry:	M16 resin-coated metal cable gland
Dimmer type:	Push on request
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	H05RN-F 3x1mm <sup>2</sup>
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

### OPTICAL:

Beam angle:	65°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Reflector in anti-UV technopolymer with super pure aluminum metallization




### LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED	DOB
Light source:	8 W
Nominal LED emission:	656 lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	110-277V
Color rendering index:	CRI>80
Luminaire emission:	1 x 525lm
LED / Bulb	Included



H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	6.3	10	21
4	5.1	16	33
3	3.8	28	58
2	2.5	64	131
1	1.3	255	524





H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	6.3	10	21
4	5.1	16	33
3	3.8	28	58
2	2.5	64	131
1	1.3	255	524

### FINISH OPTIONS:

#### Standard Finishes

●.05 Anthracite grey (matt)

●.19 Light grey (matt)

#### Upon Request Finishes

●.01 White (matt)

●.45 Corten (matt)

●.62 Antique grey (matt)

●.80 Sand (matt)

●.02 Black (matt)

●.26 Luxury bronze

●.65 Blue (matt)

●.83 Green (matt)

### ACCESSORIES:



IP 68 fast connector 4P  
AC204



Stake 170mm  
AC203



Hood MegaSegno  
AC660

### DIMMING TYPE:

- 101. Non-dimmable
- 102. 0-10V dimmable



sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake  
Dr Richland, MI  
49083 USA

### CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	70mm(2.75")
Height / Projection:	70mm(2.75")

### ELECTRICAL:

### GH1110.LVFT400EN




Number of heads:	1
Description:	1 x 8 W LED 4000 K CRI>80 1 x 690 lm
Luminaire efficiency:	58.68 lm/W
Fixture consumption:	9.41 W
Operation Range:	110-277 V - 50/60 Hz
Number of circuits:	1
Driver positioning:	Remote
Control gear type:	Electronic
Cable entry:	M16 resin-coated metal cable gland
Dimmer type:	Push on request
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	H05RN-F 3x1mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

### OPTICAL:

Beam angle:	65°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Reflector in anti-UV technopolymer with super pure aluminum metallization




### LIGHTING SOURCE,

Light source:	LED
Type of bulb or LED	DOB
Light source:	8 W
Nominal LED emission:	690 lm
Color temperature:	4000K
Binning:	Step MacAdam 3
LED voltage range:	110-277V
Color rendering index:	CRI>80
Luminaire emission:	1 x 552lm
LED / Bulb	Included



H(m)	φ (m)	lux med. 4000 K	lux max. 4000 K
5	6.3	11	22
4	5.1	17	34
3	3.8	30	61
2	2.5	67	138
1	1.3	268	552





H(m)	φ (m)	lux med. 4000 K	lux max. 4000 K
5	6.3	11	22
4	5.1	17	34
3	3.8	30	61
2	2.5	67	138
1	1.3	268	552

### FINISH OPTIONS:

#### Standard Finishes

● .05 Anthracite grey (matt)

● .19 Light grey (matt)

#### Upon Request Finishes

● .01 White (matt)

● .45 Corten (matt)

● .62 Antique grey (matt)

● .80 Sand (matt)

● .02 Black (matt)

● .26 Luxury bronze

● .65 Blue (matt)

● .83 Green (matt)

### ACCESSORIES:



IP 68 fast connector 4P  
AC204



Stake 170mm  
AC203



Hood MegaSegno  
AC660

### DIMMING TYPE:

101. Non-dimmable

102. 0-10V dimmable



sales@gordonbullard.com  
www.bullardbollards.com  
1-877-964-4646



991 South Gull Lake  
Dr Richland, MI  
49083 USA