



**BULLARD  
BOLLARDS**  
Think Bullard Think Bullard

# THE RIDGE

## Park/Urban/Garden Pole Luminaires





FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



**GENERAL INFORMATION:**

THE RIDGE is suitable for floor, wall, ground spike, or pole mounting installations. The range is available in four sizes and is designed for the illumination of façades, small and medium trees, shrubs, statues, columns, and architectural elements in general. A wide selection of optics allows precise and flexible lighting control. The body and diffuser retaining ring are manufactured from high oxidation-resistant aluminum alloy, treated with nano-bonderite and finished with textured polyester powder coating to ensure resistance to atmospheric agents and UV radiation.

Sealing is ensured by silicone gaskets, providing reliable protection under all operating and temperature conditions. The diffuser is made of ultra-transparent tempered sodium-calcium glass to maximize luminous efficiency and features a silk-screened border. All external fastening screws are in stainless steel.

**FIXTURE TYPE:**

Urban Luminaires

**LIGHTING**

LED



**VOLTAGE:**

110-277 V



**MATERIAL:**

High oxidation-resistant aluminum alloy

**CRI:**

>90

**IP RATING:**

IP 66

**IK RATING:**

IK 10

**BUILT FOR THE STORM**



sales@gordonbullard.com

www.bullardoutdoor.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T100.00.2600

**-ABST.300**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 3000K / 588 lm

Luminaire efficiency: 70.3 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X521



OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics

**-ABMT.300**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 3000K / 588 lm

Luminaire efficiency: 65.8 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X487



OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

1

**MODELS:**

CODE -T100.00.2600

**-ABFT.300**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 3000K / 588 lm

Luminaire efficiency: 61.8 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X458



OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics

**-ABET.300**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 3000K / 588 lm

Luminaire efficiency: 67.9 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X503



OPTICAL:

Beam angle: 14°x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics

FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T100.00.2600

**-ABST.400**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 4000K / 654 lm

Luminaire efficiency: 78.2 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X580



OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics

**-ABMT.400**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 4000K / 654 lm

Luminaire efficiency: 73.1 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X542



OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T100.00.2600

**-ABFT.400**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 4000K / 654 lm

Luminaire efficiency: 68.8 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X510



OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics

**-ABET.400**

DIMENSIONS:

Length: 4.21" [10.7 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]


LIGHT SOURCE:

LED / 6.3 W / 4000K / 654 lm

Luminaire efficiency: 75.5 lm/W

Fixture consumption: 7.4 W

Luminaire emission[lm]: 1X559



OPTICAL:

Beam angle: 14°x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

1


**MODELS:**

CODE -T150.00.2601

**-CCST.300**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 3000K / 982 lm  
 Luminaire efficiency: 70.5 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X871


OPTICAL:

Beam angle: 12°  
 Light distribution: Symmetrical narrow beam (<=15°)  
 Beam directionability: Fixed optics

**-CCMT.300**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 3000K / 982 lm  
 Luminaire efficiency: 65.9 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X814

OPTICAL:

Beam angle: 25°  
 Light distribution: Symmetrical medium flood (15°-45°)  
 Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

1


**MODELS:**

CODE -T150.00.2601

**-CCFT.300**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 3000K / 982 lm  
 Luminaire efficiency: 62 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X765


OPTICAL:

Beam angle: 50°  
 Light distribution: Symmetrical wide beam (45°-125°)  
 Beam directionability: Fixed optics

**-CCET.300**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]




LIGHT SOURCE:

LED / 10.5 W / 3000K / 982 lm  
 Luminaire efficiency: 68 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X840

OPTICAL:

Beam angle: 14°x 47°  
 Light distribution: 2 Axis symmetrical  
 Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60


**1 MODELS:**

CODE -T150.00.2601

**-CCST.400**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 4000K / 1090 lm  
 Luminaire efficiency: 78.2 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X967


OPTICAL:

Beam angle: 12°  
 Light distribution: Symmetrical narrow beam (<=15°)  
 Beam directionability: Fixed optics

**-CCMT.400**

DIMENSIONS:

Length: 4.21" [10.7 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 4000K / 1090 lm  
 Luminaire efficiency: 73.1 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X904

OPTICAL:

Beam angle: 25°  
 Light distribution: Symmetrical medium flood (15°-45°)  
 Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

1


**MODELS:**

CODE -T150.00.2601

**-CCFT.400**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 4000K / 1090 lm  
 Luminaire efficiency: 68.8 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X850


OPTICAL:

Beam angle: 50°  
 Light distribution: Symmetrical wide beam (45°-125°)  
 Beam directionability: Fixed optics

**-CCET.400**

DIMENSIONS:

Length: 6.29" [16 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 10.5 W / 4000K / 1090 lm  
 Luminaire efficiency: 75.5 lm/W  
 Fixture consumption: 12.4 W  
 Luminaire emission[lm]: 1X932

OPTICAL:

Beam angle: 14°x 47°  
 Light distribution: 2 Axis symmetrical  
 Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-FPST.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 3000K / 1964 lm

Luminaire efficiency: 73 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1741

OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics


**-FPMT.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 3000K / 1964 lm

Luminaire efficiency: 68.2 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1628

OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-FPFT.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 3000K / 1964 lm

Luminaire efficiency: 64.1 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1531

OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics


**-FPET.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 3000K / 1964 lm

Luminaire efficiency: 70.4 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1680

OPTICAL:

Beam angle: 14° x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-EBST.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 3000K / 2946 lm

Luminaire efficiency: 71.8 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2612

OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics


**-EBMT.300**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 3000K / 2946 lm

Luminaire efficiency: 67.2 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2442

OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics

FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-EBFT.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 3000K / 2946 lm

Luminaire efficiency: 63.1 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2296

OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics


**-EBET.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 3000K / 2946 lm

Luminaire efficiency: 69.3 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2520

OPTICAL:

Beam angle: 14° x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-FPST.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 4000K / 2180 lm

Luminaire efficiency: 81 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1933

OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics


**-FPMT.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 4000K / 2180 lm

Luminaire efficiency: 75.7 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1807

OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-FPFT.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 4000K / 2180 lm

Luminaire efficiency: 71.2 lm/W

Fixture consumption: 23.9 W

Luminaire emission[lm]: 1X1699

OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics


**-FPET.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 21 W / 4000K / 2180 lm

Luminaire efficiency: 78.2 lm/W

Fixture consumption: 23.9 W


Luminaire emission[lm]: 1X1865

OPTICAL:

Beam angle: 14°x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

1

**MODELS:**

CODE -T300.00.2602


**-EBST.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 4000K / 3270 lm

Luminaire efficiency: 79.7 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2900

OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics


**-EBMT.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 4000K / 3270 lm

Luminaire efficiency: 74.5 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2711

OPTICAL:

Beam angle: 25°

Light distribution: Symmetrical medium flood (15°-45°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60

**1 MODELS:**

CODE -T300.00.2602


**-EBFT.400**

DIMENSIONS:

Length: 13.07" [33.2 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 32 W / 4000K / 3270 lm

Luminaire efficiency: 70.1 lm/W

Fixture consumption: 36.4 W

Luminaire emission[lm]: 1X2549

OPTICAL:

Beam angle: 50°

Light distribution: Symmetrical wide beam (45°-125°)

Beam directionability: Fixed optics

CODE -T400.00.2603


**-EBST.300**

DIMENSIONS:

Length: 16.73" [42.5 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 31.5 W / 3000K / 2946 lm

Luminaire efficiency: 73 lm/W

Fixture consumption: 35.8 W

Luminaire emission[lm]: 1X2549

OPTICAL:

Beam angle: 12°

Light distribution: Symmetrical narrow beam (<=15°)

Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



sales@gordonbullard.com  
 www.bullardoutdoor.com  
 1-877-964-4646



991 South Gull Lake Dr  
 Richland, MI 49083  
 USA

**HOW TO ORDER:**

**CODE:**

Example:  
 CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
 T100.00.2600-  
 ABST.300-AG-AC60


**1 MODELS:**

CODE -T400.00.2603

**-EBET.300**

DIMENSIONS:

Length: 16.73" [42.5 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 31.5 W / 3000K / 2946 lm  
 Luminaire efficiency: 70.4 lm/W  
 Fixture consumption: 35.8 W  
 Luminaire emission[lm]: 1X2520


OPTICAL:

Beam angle: 14° x 47°  
 Light distribution: 2 Axis symmetrical  
 Beam directionability: Fixed optics

**-EBMT.400**

DIMENSIONS:

Length: 16.73" [42.5 cm]  
 Width: 1.69" [4.3 cm]  
 Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 31.5 W / 4000K / 3270 lm  
 Luminaire efficiency: 75.7 lm/W  
 Fixture consumption: 35.8 W  
 Luminaire emission[lm]: 1X2711

OPTICAL:

Beam angle: 25°  
 Light distribution: Symmetrical medium flood (15°-45°)  
 Beam directionability: Fixed optics



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



**HOW TO ORDER:**

**CODE:**

Example:  
CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
T100.00.2600-  
ABST.300-AG-AC60

**1 MODELS:**

CODE -T400.00.2603


**-EBET.400**

DIMENSIONS:

Length: 16.73" [42.5 cm]

Width: 1.69" [4.3 cm]

Height/Projection (H): 3.54" [9 cm]



LIGHT SOURCE:

LED / 31.5 W / 4000K / 3270 lm

Luminaire efficiency: 78.2 lm/W

Fixture consumption: 35.8 W

Luminaire emission[lm]: 1X2797

OPTICAL:

Beam angle: 14° x 47°

Light distribution: 2 Axis symmetrical

Beam directionability: Fixed optics

**2 FINISH OPTIONS:**

STANDARD FINISHES

**-AG** Anthracite grey(matt)

**-LG** Light grey(matt)



CUSTOM REQUEST FINISHES

**-WM** White matt

**-BR** Bronze

**-AGM** Antique grey matt

**-SM** Sand matt

**-BM** Black matt

**-CM** Corten matt

**-BLM** Blue matt

**-GM** Green matt



sales@gordonbullard.com

www.bullardoutdoor.com


1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA



FIXTURE TYPE: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES:

-T100.00.2600



-T150.00.2601



-T300.00.2602



-T400.00.2603



**HOW TO ORDER:**

**CODE:**

Example:  
CODE: BB-RD-GN-PL-T100.00.2600-ABST.300-AG-AC60

BB-RD-GN-PL-  
T100.00.2600-  
ABST.300-AG-AC60

**3 ACCESSORIES**

-AC60

-AC76

-AC89

-AC96

-AC97



sales@gordonbullard.com  
www.bullardoutdoor.com  
1-877-964-4646



991 South Gull Lake Dr  
Richland, MI 49083  
USA