



## CODE:

GH1982.FAXT300EN

## GENERAL INFORMATION:

Application field: Porch, balconies & terraces, Pathios, Covered entrances & walkways, Tables

## CONSTRUCTIVE & DIMENSIONAL:

Construction material: Aluminum  
 External screws: Stainless steel A4-70 treated with highly antioxidant water repellent lubricating solution  
 Diameter: 325mm(12,79")  
 Height: 1700mm(66,92")

## ELECTRICAL:

Description: 1 x 12 W LED 3000 K CRI>85 1300 lm  
 Operating Power: 110-277V/50-60HZ  
 Number of heads: 1  
 Number of circuits: 1  
 Driver positioning: Integral  
 Control gear type: Electronic  
 Cord length: 5m  
 Emergency kit: not available

## OPTICAL:

Beam type: Table-Floor Lamp  
 Light distribution: Light distribution diffused  
 Beam directionability: Fixed  
 Diffuser material: Polycarbonate  
 Diffuser finish: Clear  
 Diffuser temperature [°C]: < 40°C / 104°F

## LIGHT SOURCE:

Light source: LED  
 Power: 12W  
 ZVEI - LED Type: DOB  
 Color temperature: 3000K  
 Color rendering index: CRI>85  
 Nominal LED emission: 1300 lm  
 Light source: Included  
 Ambient temperature operating range: -20 °C ÷ +35 °C

## FINISH CODES:

 .01 White (matt)	 .02 Black (matt)	 .05 Dark grey (matt)
 .19 Light Grey	 .25 White & Gold	 .26 Luxury Bronze
 .62 Antique Grey	 .71 White & Red	 .80 Sand

