



**BULLARD
BOLLARDS**
Think Bullard Think Bullard



THE PHANTOM

ILLUMINATED BOLLARDS

Fixture Type:

Project Name:



General Information:

The Phantom is a modern Illuminated Security Bollard designed to bring sleek architectural lighting to outdoor spaces. Crafted from brushed stainless steel with an IP65 rating, it delivers both durability and contemporary elegance. Its distinctive angled top and soft arc LED neon glow create a sophisticated visual effect while providing functional pathway illumination. Built for high visual comfort and all-weather performance, The Phantom is ideal for luxury residential and commercial landscapes.

Fixture Type:

Illuminated Security & Safety Bollard

Lighting:

LED

Voltage:

110-277V

Material:

Stainless Steel

Top Angle:

30°

Driver Position:

Integral

IP Rating:

IP 65

Appliance Class:

I

Lighting Distribution:

360°

Warranty:

LED lighting products are warranted for 5 years.

Main Features:

High visual comfort
Functional and minimalistic design
Shock-resistant construction
Operating Temperature: -104°F to +140°F.



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

THINK BOLLARD - THINK BULLARD

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA




**BULLARD
BOLLARDS**
Think Bullard Think Bullard

**CODE:
BB-PHNTM-GL**

Fixture Type:

Project Name:



HOW TO ORDER:

CODE:

CODE EXAMPLE:

BB-PHNTM-GL-D1-H1-LSB6-K22-316-DIM

**BB-PHNTM-GL-
D1-H1-LSB6-
K22-316-DIM**

1

BOLLARD DIAMETER:

- D1 Ø: 6" (15.2 cm)
- D2 Ø: 8" (20.3 cm)
- D3 Ø: 10" (25.4 cm)
- D4 Ø: 12.2" (31 cm)
- CUS Custom Diameter

2

BOLLARD HEIGHT:

- H1 H: 42" (106.6 cm)
- H2 H: 43" (109.2 cm)
- H3 H: 44" (111.7 cm)
- H4 H: 45" (114.3 cm)
- H5 H: 46" (116.8 cm)
- H6 H: 47" (119.3 cm)
- CUS Custom Height

3

LIGHT SOURCE OUTPUT BOLLARD:

- LSB6 6 W / 396 lm
- LSB9 9 W / 580 lm
- LSB10 10 W / 590 lm
- LSB15 15 W / 880 lm
- LSB20 20 W / 1280 lm
- LSBC Custom Lumen packages on request*

4

CCT:

- K22 2200K
- K30 3000K
- K35 3500K
- K40 4000K
- K50 5000K

5

FINISH OPTIONS:

- 316 Stainless Steel Brushed Finish
- CUS Custom on request*

6

DIMMING OPTIONS:

- NON NON-Dimmable
- DIM 0-10V



Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

THINK BOLLARD - THINK BULLARD

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA